

# DigitalPersona® 5300 Reader

## FIPS 201/PIV, FAP 30 Certified USB Fingerprint Reader

The HID DigitalPersona® 5300 is a compact optical single fingerprint reader meeting both FIPS 201/PIV and FBI Mobile ID FAP 30 standards. The reader is designed to meet the high-volume requirements of large-scale Civil ID and commercial enrollment and authentication applications. Incorporating a durable IP64-rated glass platen that is also highly resistant to chemical and physical damage, the DigitalPersona 5300 is well suited for harsh environments.

The reader rapidly captures and produces fingerprint images at 500 dpi resolution in ANSI and ISO/IEC standard formats. On-board electronics automatically control calibration and data transfer over the USB interface. The DigitalPersona 5300 can be used with any standards-compatible fingerprint template extractor or matcher, including the DigitalPersona FingerJet Biometric Engine. The DigitalPersona 5300 and the FingerJet Biometric Engine provide an unmatched ability to authenticate even the most difficult fingerprints accurately and rapidly.



### APPLICATIONS

Enrollment and authentication for:

- Voter registration
- National ID
- Benefits entitlement
- Microfinance and healthcare
- Network and application access

### FEATURES

- FIPS 201/PIV certified
- Mobile ID FAP 30 certified
- 500 dpi images
- Compact size
- Live Finger Detection
- Compatible with DigitalPersona SDKs for Windows®, Linux® and Android®

# DigitalPersona® 5300 Reader



<b>Product Name</b>	<b>DigitalPersona® 5300 Reader</b>
<b>Dimensions</b>	86mm L x 53mm W x 31mm H (+/-0.5mm)
<b>Scan Capture Area</b>	20.32 mm x 25.4 mm
<b>Live Finger Detection (LFD)</b>	Configurable using the Digital Persona Biometric Software Developer Kit (SDK)
<b>Image Mode</b>	Uncompressed Image Mode (raw) WSQ Compressed
<b>Pixel Resolution</b>	500 dpi
<b>Power Supply Voltage</b>	5.0V ±5%
<b>Power Supply Current - Scanning</b>	< 150 mA (Typical)
<b>Power Supply Current - Idle Mode</b>	< 40 mA (Typical)
<b>Power Supply Current - Suspend Mode</b>	< 0.5 mA (Maximum)
<b>Temperature, Operating</b>	-10° - 55° C
<b>Humidity, Operating</b>	0% - 90% non-condensing
<b>Temperature, Storage</b>	-20° - 55° C
<b>Humidity, Storage</b>	0% - 90% non-condensing
<b>Scan Data</b>	8-bit grayscale (256 gray levels)
<b>Top Surface</b>	IP64-rated seal between top case and glass surface*
<b>Interface</b>	USB 2.0 High Speed
<b>Weight</b>	245 grams
<b>Standards Compliance</b>	FIPS 201 PIV, Mobile ID FAP 30, RoHS, UL, USB, WEEE, FCC, CE
<b>ESD</b>	IEC61000-4-2 Level 3

Data subject to change without notice.

\*IP64 rating is for the seal between the top case and the glass imaging window. Devices containing the embedded module must seal the module top case to their chassis or housing to extend the IP64 protection to the device.

\*\*This reader/module uses Microsoft's Windows native USB Video Class Driver. HID does not provide a separate WHQL driver.

For more information, please [click here](#).



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

For more global phone numbers [click here](#)

© 2021 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2021-09-07-eat-digitalpersona-5300-reader-ds-en

PLT-04457

Part of ASSA ABLOY